

UST-HQ1500

Updated Product

STANDARD PARAMETER	
Function and Use	Compact, powerful hydraulic press for crimping connector
Compression Range	
Compression Range for ACSR Conductor	450-500 MCM
Compression Range for Aerial Conductor	300-600 MCM
Structure	Sturdy and compact
Crimping Force	15 Ton
Application	Crimping
Crimping Type	Aerial / Hexagonal
Dies	Copper and Aluminum
Operating Pressure	10,000 PSI
Piston Stroke	28 mm
Weight	3.7 lbs.



220V AC ELECTRIC MOTOR WITH 700BARS HYDRAULIC PUMP

Function and use

Generating a pressure of 700/10 000 PSI with 220V hydraulic pump. 550 W single-phase 220 V 50 Hz motor with starting capacitor

- Nominal Pressure: 700 bars / 10 000 PSI.
- Flow rate: 0,8L/min - 0.21 gal/min
- Tank: 2L oil / 0.53 gal
- Hydraulic oil supplied: TOTAL Equivis XV 32
- Weight: 17 kg / 37,4 lbs.



Function and use

Robust plastic shell with IP 42 protection level.

Emergency manual pressure release.

Hydraulic reservoirs drain or fill plug.

- Nominal Pressure: 700 bars / 10 000 PSI.
- Flow rate: 1L/min - 0,15Umin - 0.2642 gal/min - 0.0396 gal/min
- Tank: 0.8 oil / 27 oz.
- Hydraulic oil supplied: TOTAL Equivis XV 32
- Weight: 5.7kg / 12,5 lbs.
- Dimensions: 330 x 160 x 250 mm / 13 x 6 x 10 in



Note: For Quality Reason, we have the right to change the color or design of the tools without any prior notice.



US Tool LLC. USA
 850, Pomfret Road, Hampton, CT 06247. USA.

